


Rugged Mobile PC

M10A



- Powered by 12th Generation Intel® Core™ i5-1235U/i7-1255U Processor and Windows 11
- Support 16GB RAM + 128GB SSD, the SSD is detachable, easy to expand by simply pulled out and replaced
- 10.1-inch LCD screen with 700 nits high brightness
- 10-point capacitive touch, support glove touch
- Supports the latest WiFi 6 technology, 4G and Bluetooth 5.1
- 7.4V/5000mAh + 7.4V/860mAh double battery, the large battery is removable and hot-swappable
- Equipped with a full set of interfaces including full-featured Type-C, USB 3.1, 2.1a Mini HDMI and more
- Choose one of four modules among wired network interface, USB 2.0, RS232 and 2D barcode module, choose as you like
- Passed IP65 and multiple stringent MIL-STD-810H military standard tests, industrial-grade safety protection



12th Gen Intel Processors



Windows 11



10.1-inch screen



700 nits highlighting




Wi-Fi 6/BT 5.1/4G



16GB RAM
128GB SSD



Dual battery life



Rich interface
expansion



Four-choice
module bit



IP65 protection level

M10A Rugged Mobile PC

Specifications

 **CPU**
12th Generation Intel® Core™
i5-1235U/i7-1255U Processor

 **System**
Windows 11

 **Memory**
RAM 16GB DDR4L
ROM 128GB SSD


 **Display**
Type: LCD
Size: 10.1 inch 16:10
Resolution: 1200*1920
Brightness: 700cd/m²

 **Touch Panel**
10 points capacity TP G+G
Hardness over 7H

 **Dimension/Weight**
292.1*192.1*28.9mm
1290g

 **Buttons**
Power *1
Volume Key + *1
Volume Key - *1
Windows Home *1
F Key *1

 **Speaker**
6Ω/1W
Waterproof Speaker *1

 **Battery**
7.4V/860mAh(Small Battery)
Build in Lithium-ion
polymer battery, Non-removable
7.4V/5000mAh (Big Battery)
Removable Li-polyment Battery


 **Internet**
4G/Wi-Fi 6/BT5.1


 **GPS**
Support:
GPS, Beidou, glonass

 **Data Collection**
NFC (Optional)
Fingerprint (Built-in)

 **Certification**
IP65

 **Adapter**
DC 19V 3.42A

 **Rugged Features**
MIL-STD-810H: 1.22m drop
Working temperature: -20 °C to 60 °C
Storage temperature: -30 °C to 70 °C
Humidity: 95% Non-Condensing
Electrostatic discharge:
± 8kV contact discharge
± 15kV air discharge

 **I/O Interface**
USB 3.1 *1、Type C *1
ϕ 3.5mm *1
TF/SIM *1、DC *1
HDMI 2.1a mini *1
12PIN Pogo Pin *1
Expansion Module:
RJ45(10/100M) *1/RS232 *1
USB2.0 *1/QR Code Scanner



* The technical specifications of this product are subject to change without prior notice